

Deemax DH

ASTM CATEGORY 5 : extreme offroad
Recommended tyre sizes: 50 to 76 mm (2.0" to 3.0")

参照ホイール

P84751	DmxDH27,518Pr	F73371	DmxDH1827,5Ft





RIMS


 :

1	V2318810	KIT FRONT RIM DEEMAX DH 27,5"

SPOKES

2	V2385801	KIT 14 FRONT BUTTED FLAT SPOKES 285mm

HUB SHELLS

3	N/A	HUB BODY
4	M40179	FRONT BEARING 25x37x7 20mm AXLE
5	30870501	FRONT AXLE 20mm CROSSMAX ST/SX + DEEMAX ULTI 2012

ADAPTERS

6	12982901	20mm adapter for Crossmax ST/SX (front wheel)
	12982701	9mm Adapters + QR for Crossmax ST/SX (front wheel)
	12982801	15mm ADAPTER KIT - 2012 WHEELS

Download date: 2024-03-29 / Update date: 2022-05-30

MAVIC Deemax DH

付属品

USTÂ¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿ (129 838 01)	
USTÂ¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿ (129 838 01)	
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿ (325 423 01)	
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿ (325 423 01)	
Â¿Â¿Â¿Â¿Â¿Â¿Â¿	
Â¿Â¿Â¿Â¿Â¿Â¿Â¿	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Freewheel: Shimano/Sram or XD	
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿20mmÂ¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿15mmÂ¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿	
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿20mmÂ¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿15mmÂ¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿	
Rear axle : 12x157mm, convertible to 12x150 with optional adapters	
Rear axle : 12x157mm, convertible to 12x150 with optional adapters	
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿ Â¿Â¿Â¿Â¿ Â¿Â¿Â¿Â¿Â¿	

Specifications

リム

- Â¿Â¿ : Â¿Â¿Â¿Â¿Â¿
- Â¿Â¿ : Â¿Â¿Â¿Â¿Â¿
- Â¿Â¿Â¿Â¿Â¿ : SUP
- Â¿Â¿Â¿Â¿Â¿ : SUP

Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿
Â¿Â¿Â¿Â¿ISM 4D
Â¿Â¿Â¿Â¿ISM 4D
Â¿Â¿Â¿Â¿Â¿Â¿6.5 mm
Â¿Â¿Â¿Â¿Â¿Â¿6.5 mm
Â¿Â¿Â¿Â¿UST
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿
Â¿Â¿Â¿Â¿UST
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿
Â¿Â¿28 mm
Â¿Â¿28 mm
Â¿Â¿Â¿Â¿Â¿Â¿Â¿
Â¿Â¿Â¿Â¿Â¿Â¿Â¿

- ETRTO Â¿Â¿Â¿ 27.5" : 584x28TSS
- ETRTO Â¿Â¿Â¿ 27.5" : 584x28TSS

スポーク

Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿
Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿

- Shape : straight pull, flat rear and flat, double butted front
- Shape : straight pull, flat rear and flat, double butted front

Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿Â¿