

MAVIC Deemax Pro

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 120kg, bike included
Recommended tyre sizes: 44 to 76 mm (1.75" to 3.0") rear and 50 to 76 mm (2.0" to 3.0") front

REFERENCES WHEELS

F80411	Deemax Pro 18 27,5 Ft Bst	F80401	Deemax Pro 18 27,5 Ft





RIMS



 :

1	V2319210	KIT FRONT RIM E-DEEMAX/DEEMAX PRO 27,5''

SPOKES

2	V2386101	KIT 1 FRT/1 NDS STAMPED SPOKES 275mm DEEMAX PRO - while stoc
2	36674901	KIT 12 FT XMAX END/FT-NDS DEEMAX PRO 27,5'' ALU SPK 275mm

HUB SHELLS

3	N/A	HUB BODY
4	M40179	FRONT BEARING 25x37x7 20mm AXLE
5	30870501	FRONT AXLE 20mm CROSSMAX + DEEMAX ULTI 2012
7	N/A	HUB BODY
8	99688501	BEARING KIT 9/12/15 D6T HUB 20x32x7 6804
9	V2370701	KIT FRONT QRM+ AXLE BOOST INTL 110mm

OPTIONS

	V2650201	ADAPTER Front Torque Cap 15x31 MTB QRM +

ADAPTERS

6	12982901	ADAPTER Ft 20x110mm
10	B4104401	ADAPTER Ft 15mm QRM+
	B4104301	ADAPTER Ft 9mm QR QRM+
	12982801	ADAPTER Ft 20 to 15mm
	12982701	ADAPTER Ft 20 to 9mm QR incl.

Download date: 2024-03-29 / Update date: 2022-05-30

MAVIC Deemax Pro

DELIVERED WITH

Front 15 mm adapters (129 828 01)	
UST valve and accessories (129 838 01)	
Multifonction adjustment wrench (325 423 01)	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Front axle: 20mm, convertible to 15mm thru axle with included adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- **Material :** Maxtal
- **Drilling :** Fore
- **Weight reduction :** ISM 4D
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 28 mm front and 25mm rear
- **ETRTO size 27.5" :** 584x28TSS front & 584x25TSS rear

Hookless profile

SPOKES

- **Material :** Zicral
- **Shape :** straight pull, bladed
- **Nipples :** Fore integrated aluminum
- **Count :** 24 front and rear
- **Lacing :** front crossed 2, rear Isopulse

WHEEL HUB

- **Front and rear bodies :** aluminum

Adjustable sealed cartridge bearings (QRM+)

- **Freewheel :** ITS-4 alloy

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)

WHEEL WEIGHTS

810

Download date: 2024-03-29 / Update date: 2022-05-30