2019 FRONT


ASTM CATEGORY 3: CROSS COUNTRY AND TRAIL RIDING

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't

exceed 120kg, bike included

Recommended tyre sizes: 46mm to 64mm (1.8" to 2.5")

REFERENCES WHEELS





RIMS



:

1	V3761215	KIT FRT/REAR RIM CROSSMAX LIGHT 19 29"
	V2700101	UST Tape 28mm for 25 to 27mm wide rims

SPOKES

2 V23	385401	KIT 12 FT/NDS CROSSMAX LIGHT 29" SPK 296mm
--------------	--------	--

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2372301	KIT 100mm AXLE QRM AUTO MTB > 2019
7	N/A	HUB BODY
8	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019

OPTIONS

ADAPTERS

6	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	99694101	ADAPTER Et 15 to 9mm QR



DELIVERED WITH

Front QR adapters (non-boost wheel)	
Rear QR adapters (non-boost wheel)	
Tubeless rim tape	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Rear axle: 12mm thru axle, convertible to Quick Release with adapters (delivered with non-boost wheel)	
Freewheel: Shimano Micro Spline	

Specifications

RIMS

Material: \$6000 Aluminum
 Joint: welded
 Drilling: traditional
 Valve hole diameter: 6.5 mm
 Tyre: UST Tubeless and tubetype

• ETRTO size 27.5": 584x25TSS
• ETRTO size 29": 622x25TSS
Hookless profile

Use with Mavic Tubeless Tape

SPOKES

- Material : steel

Shape: straight pull, round
 Count: 24 front and rear
 Lacing: front and rear crossed 2

WHEEL HUB

 ${\color{red} \bullet}$ Front and rear bodies : ${\color{gray} \text{aluminum}}$

- Axle material : aluminum

Auto adjust sealed cartridge bearings (QRM Auto),

front and rear

• Freewheel: Instant Drive 360 steel

VERSIONS

■ Disc standard: 6 Bolts only

- Hub width: Boost (front 110, rear 148) or Non-

Boost (front 100, rear 135/142)
• Freewheel: Shimano/Sram or XD

WHEEL WEIGHTS