
MAVIC E-Crossmax

ASTM CATEGORY 3 : CROSS COUNTRY AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 150kg, bike included
Recommended tyre sizes: 60mm to 76mm (2.35" to 3.0")

REFERENCES WHEELS

R25511	E-Xmax 27,5 Rr XD	R25491	E-Xmax 27,5 Rr
R25531	E-Crossmax 27,5 Rr Boost XD	R25521	E-Crossmax 27,5 Rr Boost



RIMS



 :

1	V3763115	KIT FRT/REAR RIM E-CROSSMAX 27,5''
	V3750101	35mm UST Green Tape for 30mm wide rims

SPOKES

2	V3821301	KIT 14 FRT/NDS E-CROSSMAX/E-XA 27,5'' FLAT SPOKE 282mm + nip
3	V3821501	KIT 14 DS E-CROSSMAX/E-XA 27,5'' FLAT SPOKE 280mm + nippl.

HUB SHELLS

4	N/A	HUB BODY
5	M40076	HUB BEARINGS 17x30x7 6903 x 2
6	V2372101	KIT ID360 135/142 D6T AXLE WITH CLIP
7	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
8	V2251601	KIT ID360 SEAL + GREASE
9	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
10	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
11	V2372901	KIT 3 ID360 MTB SPRINGS
12	V3790101	HG9 Steel MTB Freewheel Body ID360
13	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
15	N/A	HUB BODY
16	V2372201	KIT ID360 148 D6T AXLE WITH CLIP

ADAPTERS

14	V2510701	ID360V2RrAxleAdapt12x142/148
	V2510801	ID360 V2 RrAxleAdapt9x135

Download date: 2024-03-29 / Update date: 2022-04-14

MAVIC E-Crossmax

DELIVERED WITH

Front QR adapters (non-boost wheel)	
Rear QR adapters (non-boost wheel)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Specific disc bolts (308 719 01)	
Specific disc bolts (308 719 01)	
Tubeless rim tape	
Tubeless rim tape	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Freewheel: Shimano/Sram or XD	
Freewheel: Shimano Micro Spline	
Freewheel: Shimano Micro Spline	

Specifications

RIMS

- **Material :** S6000 Aluminum
- **Material :** S6000 Aluminum
- **Joint :** sleeved
- **Joint :** sleeved
- **Drilling :** traditional
- **Drilling :** traditional

E-Bike specific rim profile
E-Bike specific rim profile

- **Valve hole diameter :** 6.5 mm
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 30 mm
- **Internal width :** 30 mm

Hookless profile
Hookless profile
Use with Mavic Tubeless Tape
Use with Mavic Tubeless Tape

- **ETRTO size 27.5" :** 584x30TSS
- **ETRTO size 27.5" :** 584x30TSS
- **ETRTO size 29" :** 622x30TSS
- **ETRTO size 29" :** 622x30TSS

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** straight pull, round
- **Shape :** straight pull, round
- **Count :** 28 front and rear
- **Count :** 28 front and rear
- **Lacing :** front and rear crossed 3
- **Lacing :** front and rear crossed 3

WHEEL HUB

- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Axle material :** aluminum
- **Axle material :** aluminum

Auto adjust sealed cartridge bearings (QRM Auto), front and rear
Auto adjust sealed cartridge bearings (QRM Auto), front and rear

- **Freewheel :** Instant Drive 360 steel
- **Freewheel :** Instant Drive 360 steel

VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only
- **Disc standard :** 6 Bolts only
- **Hub width :** Boost only (front 110, rear 148)
- **Hub width :** Boost only (front 110, rear 148)
- **Freewheel :** Shimano/Sram or XD
- **Freewheel :** Shimano/Sram or XD

WHEEL WEIGHTS

Weight Rear 27.5": 1123
Weight Rear 29": 1160

Download date: 2024-03-29 / Update date: 2022-04-14