
# Crossmax Elite 29 19




ASTM CATEGORY 3 : CROSS COUNTRY AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 120kg, bike included
Recommended tyre sizes: 36 mm to 64 mm (1.4" to 2.5")

## REFERENCES WHEELS

| | | | |
|---|---|---|---|
| F83091 | Xmax Elite 29 19 Ft | F83101 | Xmax Elite 29 19 Ft Boost |




## RIMS



 :

| | | |
|---|---|---|
| 1 | V3760515 | KIT FRT/REAR RIM CROSSMAX ELITE 19 29'' While Stocks lasts |
| | V2620101 | UST RIM TAPE 25mm (for 21-24mm wide rim) |

## SPOKES

| | | |
|---|---|---|
| 2 | V2386701 | KIT 12 FRT CROSSMAX ELITE/XA ELITE 19 29'' BUTTED SPOKE 297m |

## HUB SHELLS

| | | |
|---|---|---|
| 3 | N/A | HUB BODY |
| 4 | V2500901 | KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP |
| 5 | V2372301 | KIT 100mm AXLE QRM AUTO MTB > 2019 |
| 7 | N/A | HUB BODY |
| 8 | V2372401 | KIT 110mm AXLE QRM AUTO MTB > 2019 |

## OPTIONS

| | | |
|---|---|---|
| | V2374401 | TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB |

## ADAPTERS

| | | |
|---|---|---|
| 6 | V2372501 | 15mm MTB Axle Cap QRM Auto From 2019 |
| | 99694101 | ADAPTER Ft 15 to 9mm QR |

Download date: 2024-03-28 / Update date: 2022-04-14

# MAVIC Crossmax Elite 29 19

2019
FRONT

## DELIVERED WITH

| | |
|---|---|
| Front QR adapters (non-boost wheel) | |
| Front QR adapters (non-boost wheel) | |
| Rear QR adapters (non-boost wheel) | |
| Rear QR adapters (non-boost wheel) | |
| UST valve and accessories (129 838 01) |  |
| UST valve and accessories (129 838 01) |  |
| Tubeless rim tape | |
| Tubeless rim tape | |

## COMPATIBILITY

| | |
|---|---|
| Freewheel: Shimano/Sram or XD | |
| Freewheel: Shimano/Sram or XD | |
| Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel) | |
| Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel) | |
| Rear axle: 12mm thru axle, convertible to Quick Release with adapters (delivered with non-boost wheel) | |
| Rear axle: 12mm thru axle, convertible to Quick Release with adapters (delivered with non-boost wheel) | |
| Freewheel: Shimano Micro Spline | |
| Freewheel: Shimano Micro Spline | |

## Specifications

### RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Joint :** SUP
- **Joint :** SUP
- **Drilling :** traditional
- **Drilling :** traditional
- **Weight reduction :** ISM 4D
- **Weight reduction :** ISM 4D
- **Valve hole diameter :** 6.5 mm
- **Valve hole diameter :** 6.5 mm
- **Tyre :** UST Tubeless and tubetype
- **Tyre :** UST Tubeless and tubetype
- **Internal width :** 22 mm
- **Internal width :** 22 mm
- **ETRTO size 27.5" :** 584x22TSS
- **ETRTO size 27.5" :** 584x22TSS
- **ETRTO size 29" :** 622x22TSS
- **ETRTO size 29" :** 622x22TSS

Hookless profile
Hookless profile
Use with Mavic Tubeless Tape
Use with Mavic Tubeless Tape

### SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** straight pull, flat, double butted
- **Shape :** straight pull, flat, double butted
- **Count :** 24 front and rear
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2
- **Lacing :** front and rear crossed 2

### WHEEL HUB

- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Axle material :** aluminum
- **Axle material :** aluminum

Auto adjust sealed cartridge bearings (QRM Auto), front and rear
Auto adjust sealed cartridge bearings (QRM Auto), front and rear

- **Freewheel :** Instant Drive 360
- **Freewheel :** Instant Drive 360

### VERSIONS

- **Color :** Black only
- **Disc standard :** 6 Bolts only
- **Disc standard :** 6 Bolts only
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)
- **Hub width :** Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)
- **Freewheel :** Shimano/Sram or XD
- **Freewheel :** Shimano/Sram or XD

### WHEEL WEIGHTS

Download date: 2024-03-28 / Update date: 2022-04-14