

MAVIC E-Deemax Pro 27,5

1
2019
REAR

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 150kg, bike included

Recommended tyre sizes: 50mm to 76mm (2.0" to 3.0")


REFERENCES WHEELS

R27821 E-DeemaxPro27,5 19 Rr XD

R27811 E-Deemax Pro 27,5 19 Rr

R27841 E-Dmx Pro 27,5 19 Rr Boost XD

R27831 E-Dmx Pro 27,5 19 Rr Boost



RIMS



&NBSP;:

1 V3760313 KIT REAR RIM E-DEEMAX PRO 19 27,5"

SPOKES

2 V2386101 KIT 1 FRT/1 NDS STAMPED SPOKES 275mm DEEMAX PRO - while stoc
2 V2384701 KIT 12 FT/NDS CROSSMAX PRO 27,5" SPK 275mm
3 V2386601 KIT 12 DS CROSSMAX PRO/XA PRO/E-DEEMAX PRO 19 27,5" BUTTED

HUB SHELLS

4 N/A HUB BODY
5 M40076 HUB BEARINGS 17x30x7 6903 x 2
6 V2372101 KIT ID360 135/142 D6T AXLE WITH CLIP
7 V2252701 KIT ID360 INSERT SHAPED EAR LOBE > 2017
8 V2251601 KIT ID360 SEAL + GREASE
9 V2375201 KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
10 V2375401 KIT ID360 MTB 24T 3 NOISE REDUCING PADS
11 V2372901 KIT 3 ID360 MTB SPRINGS
12 V3790101 HG9 Steel MTB Freewheel Body ID360
13 V2373001 KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
15 V2252201 KIT 2 REAR HUB RETENTION RINGS 48mm
16 N/A HUB BODY
17 V2372201 KIT ID360 148 D6T AXLE WITH CLIP

ADAPTERS

14 V2510701 ID360V2RrAxleAdapt12x142/148
V2510801 ID360 V2 RrAxleAdapt9x135



E-Deemax Pro 27,5

2019
REAR

DELIVERED WITH

Computer magnet (105 416 01)	
Computer magnet (105 416 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Specific disc bolts (308 719 01)	
Specific disc bolts (308 719 01)	
Multifunction adjustment wrench (325 423 01)	
Multifunction adjustment wrench (325 423 01)	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram or XD	
Freewheel: Shimano/Sram or XD	
Front axle: 20mm, convertible to 15mm thru axle with optional adapters	
Front axle: 20mm, convertible to 15mm thru axle with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Freewheel: Shimano Micro Spline	
Freewheel: Shimano Micro Spline	

Specifications

RIMS

- Material : Mxstal
- Material : Mxstal
- Joint : SUP
- Joint : SUP
- Drilling : Fore
- Drilling : Fore
- Weight reduction : ISM 4D
- Weight reduction : ISM 4D
- Valve hole diameter : 6.5 mm
- Valve hole diameter : 6.5 mm
- Tyre : UST Tubeless and tubetype
- Tyre : UST Tubeless and tubetype
- Internal width : 28 mm
- Internal width : 28 mm

Hookless profile
Hookless profile

- ETRTO size 27.5" : 584x28TSS
- ETRTO size 27.5" : 584x28TSS

SPOKES

- Material : Zicral
- Material : Zicral
- Shape : straight pull, flat front and rear drive side and flat, double butted rear non drive side
- Shape : straight pull, flat front and rear drive side and flat, double butted rear non drive side
- Nipples : Fore integrated aluminum
- Nipples : Fore integrated aluminum
- Count : 24 front and rear
- Count : 24 front and rear
- Lacing : front crossed 2, rear Isopulse
- Lacing : front crossed 2, rear Isopulse

WHEEL HUB

- Front and rear bodies : aluminum
- Front and rear bodies : aluminum
- Front bearings : adjustable sealed cartridge bearings (QRM+), Rear bearings auto adjust sealed cartridge bearings (QRM Auto)
- Front bearings : adjustable sealed cartridge bearings (QRM+), Rear bearings auto adjust sealed cartridge bearings (QRM Auto)
- Freewheel : Instant Drive 360 steel
- Freewheel : Instant Drive 360 steel

VERSIONS

- Color : Black only
- Disc standard : 6 Bolts only
- Disc standard : 6 Bolts only
- Hub width : Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)
- Hub width : Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142)
- Freewheel : Shimano/Sram or XD
- Freewheel : Shimano/Sram or XD

WHEEL WEIGHTS

1075