

FRONT

ASTM CATEGORY 1 : road only


For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't

exceed 120kg, bike included Recommended tyre sizes: 25 to 32 mm

Max. Pressure tubeless: 25mm 6 bars - 87 PSI, 28mm 5 bars - 70 PSI. Max pressure tubetype: 25mm 7 bars -

102 PSI, 28mm 6 bars - 87 PSI

REFERENCES WHEELS



RIMS



:

1	V2735015	KIT FRONT/REAR RIM AKSIUM ELITE UST UB SUP
	V3720101	25mm UST Tape for 19 to 22mm Road Rims

SPOKES

2	V3664701	KIT 10 FRT/NDS AKSIUM ELITE UST FLAT SPOKE 282mm + nipple
---	----------	---

HUB SHELLS

4	M40318	KIT 2 HUB BEARINGS 6001
5	99603801	SHORT EXPENSIBLE BEARING SUPPORTS > 2008
6	99603701	FRONT AXLE QRM ROAD 2008
7	12034401	KIT 3 HUB CAPS AERO 10 SLOTS BLACK

TYRES

8	39938825	Yksion Pro UST 700x25
8	39938828	Yksion Pro UST 700x28

MAVIC Aksium Elite UST

DELIVERED WITH

Mavic tyre sealant (rear wheel) (355 466 01) Tyre sealant syringe
Tyre sealant syringe
BR101 quick releases
(M40350 frt, M40351 rear road, M40352 rear
MTB)
UST valve and accessories
(129 838 01)
(123 333 3.)
Tubeless rim tape
Tubeless fill tape
User guide

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Front axle: Quick Release only	
Rear axle: Quick Release only	

Specifications

RIMS

- Material: S6000 Aluminum
- Height: 25mm
- Joint: SUP
- Drilling: traditional
- Brake track: UB Control
- Valve hole diameter: 6.5 mm
- Tyre: UST Tubeless and tubetype
- Internal width: 19 mm
- ETRTO size: 622x19TC Road

Use with Mavic Tubeless Tape

SPOKES

- Material : steel

- Shape: straight pull, flat, double butted

• Nipples: steel, ABS
• Count: 20 front and rear

• Lacing: radial front and rear non-drive side,

crossed 2 rear drive side

WHEEL HUB

• Front and rear bodies : aluminum • Axle material : steel Sealed cartridge bearings (QRM) • Freewheel : FTS-L steel WHEEL WEIGHTS

825