
# **MAVIC** Cosmic Pro Carbon SL Disc TDF


1

ASTM CATEGORY 1 : road only For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels don't exceed 120kg, bike included Recommended tyre sizes: 25 to 32 mm Max. Pressure: see indication on wheel and tyre. If they differ, use the lower of the 2

# **REFERENCES WHEELS**

F89361 CosProCarbSLUSTDCL TDF2 Ft







RIN	IS				
	:				
1	V4090910	KIT FRONT RIM COSMIC PRO CARBON SL UST DISC TdF 20			
	V2620101	UST RIM TAPE 25mm (for 21-24mm wide rim)			
SPO	SPOKES				
2	V3663501	KIT 12 BUTTED AERO STAINLESS SPOKE 277 + alu nipple + washer			
HUB SHELLS					
3	N/A	HUB BODY			
4	M40129	KIT 2 BEARINGS 6902 15x28x7			
5	V2373301	KIT QRM AUTO FRONT AXLE 12mm > 2019			
AD/	APTERS				
	V2680301	"Kit Ft Road Adapter 12 >> 9mm"			

# **MAVIC** Cosmic Pro Carbon SL Disc TDF

# **DELIVERED WITH**

Mavic tyre sealant (rear wheel)	
(355 466 01)	
Tyre sealant syringe	
Front QR adapters	
(996 941 01 for MTB or B41 043 01 for road)	
Rear QR adapters for Instant Drive 360	
(B49 894 01)	
UST valve and accessories	A
(129 838 01)	
	+
Tubeless rim tape	
User guide	
oool guluo	

# **COMPATIBILITY**

Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Front axle: 12x100 thru axle, easily convertible to quick release with included adapters. Not compatible with 15mm through axles.	
Rear axle: 12mm thru axle, convertible to Quick Release with included adapters	

# **Specifications**

#### RIMS

- Material : 3K carbon fibers
- -Height: 45 mm
- Drilling : traditional
- Disc brake specific profile - Valve hole diameter : 6.5 mm
- Tyre : UST Tubeless and tubetype
- Internal width : 19 mm
- ETRTO size : 622x19TC Road
- Use with Mavic Tubeless Tape

### SPOKES

- -Material : steel • Shape : straight pull, aero, double butted • Nipples : aluminum, ABS . Count: 20 front and 24 rear
- Lacing : front crossed 2, rear Isopulse

### WHEEL HUB

- Front and rear bodies : aluminum • Axle material : aluminum
- Auto adjust sealed cartridge bearings (QRM Auto), front and rear
- Freewheel : Instant Drive 360
- Front : Quick release and 12x100 through axle
- compatible • Rear: Quick Release, 12x142 and 12x135
- compatible

### VERSIONS

- Color : Black only - Disc standard : Center Lock(R) only

## WHEEL WEIGHTS

685