# ALLROAD PRO CARBON SL DISC

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included
Recommended tyre sizes: 28 to 64 mm (1.1" to 2.5")
Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the 2
Maximum tyre pressure: 4.4bar/64PSI with a 28mm tyre - 2.6bar/38PSI with a 64mm tyre

## REFERENZEN RÃ¤DER



## RIMS

&NBSP;:

| | | |
|---|---|---|
| **1** | V4094513 | Kit Rear rim Allroad Pro Carbon SL while stock lasts |
| **1** | V2738913 | KIT REAR RIM ALLROAD PRO CARBON SL -while stock last |
| | V2620101 | UST RIM TAPE 25mm (for 21-24mm wide rim) |

## SPOKES

| | | |
|---|---|---|
| **2** | V3821801 | KIT 12 FRT/REAR CROSSMAX PRO CARBON 29'' EXTRA FLAT SPOKE 29 |
| **2** | V3668301 | Kit 2 FRONT/NDS Allroad Pro Carbon SL stamped spoke 291 + al |
| **3** | V2384401 | KIT 12 FRONT + REAR NON-DRIVE SIDE BUTTED SPOKES 274mm CROSS |

## HUB SHELLS

| | | |
|---|---|---|
| **4** | N/A | NABENKÖRPER |
| **5** | V2560401 | KIT ID360 2 BEARINGS 17x28x7 + CIRCLIP + WAVED WASHER (QRM A |
| **6** | V2252901 | KIT ID360 CENTER LOCK 135/142mm AXLE WITH CIRCLIP |
| **7** | V2252701 | KIT ID360 INSERT SHAPED EAR LOBE > 2017 |
| **8** | V00063631 | Kit ID360 seal version 2 (larger) |
| **9** | V2251701 | ID360 2 RATCHETS + SPRING + GREASE |
| **10** | V2500501 | Kit 3 ID360 pad for noise reduction |
| **11** | V2251801 | KIT 3 ID360 ROAD SPRINGS |
| **12** | V3430101 | HG11 Freewheel Body ID360 |
| **13** | V2560501 | KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x28x7 bearing |
| **15** | V2252201 | KIT 2 REAR HUB RETENTION RINGS 48mm |

## ADAPTERS

| | | |
|---|---|---|
| **14** | V3811001 | KIT ROAD ID360 RR CL ENDCAP (12MM) |
| | V2510801 | ID360 EVO REAR AXLE ADAPTERS 9x135mm DCL & D6T |
| | V2510901 | ID360 EVO REAR AXLE ADAPTERS 12x135mm DCL & D6T |

Download date: 2024-03-29 / Update date: 2024-02-15

# ALLROAD PRO CARBON SL DISC

## GELIEFERT MIT

| | |
|---|---|
| Mavic tyre sealant (rear wheel)<br>(355 466 01) | |
| Tyre sealant syringe | |
| Front QR adapters<br>(996 941 01 for MTB or B41 043 01 for road) | |
| Rear QR adapters for Instant Drive 360<br>(B49 894 01) | |
| UST valve and accessories<br>(129 838 01) | |
| UST valve and accessories<br>(129 838 01) | |
| UST valve and accessories<br>(129 838 01) | |
| Tubeless-Felgenband | |
| Tubeless-Felgenband | |
| User guide | |
| User guide | |
| User guide | |

## COMPATIBILITY

| | |
|---|---|
| Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies | |
| Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies | |
| Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies | |
| Front axle: 12mm thru axle, easily convertible to quick release with included adapters. Convertible to 15mm with complete axle replacement | |
| Front axle: 12mm thru axle, easily convertible to quick release with included adapters. Convertible to 15mm with complete axle replacement | |
| Front axle: 12mm thru axle, easily convertible to quick release with included adapters. Convertible to 15mm with complete axle replacement | |
| HR-Achse: 12x142-mm-Steckachse, umrÃ¼stbar auf Schnellspanner (mit optionalen Adaptern und Austauschachse) | |
| HR-Achse: 12x142-mm-Steckachse, umrÃ¼stbar auf Schnellspanner (mit optionalen Adaptern und Austauschachse) | |
| Rear axle: 12mm thru axle, convertible to Quick Release with included adapters | |

## Specifications

### FELGEN

- **Material :** 100% Unidirectional carbon fiber
- **Material :** 100% Unidirectional carbon fiber
- **Material :** 100% Unidirectional carbon fiber
- **Height :** 25mm
- **Drilling :** traditional

Disc brake specific profile

- **Valve hole diameter :** 6.5 mm
- **Tire :** UST Tubeless and tubetype
- **Internal width :** 23 mm
- **ETRTO size :** 622x23TSS Road

Hookless profile

- **Height :** 25mm
- **Height :** 25mm

Use with Mavic Tubeless Tape

- **Drilling :** traditional
- **Drilling :** traditional

Disc brake specific profile

Disc brake specific profile

- **Valve hole diameter :** 6.5 mm
- **Valve hole diameter :** 6.5 mm
- **Tire :** UST Tubeless and tubetype
- **Tire :** UST Tubeless and tubetype
- **Internal width :** 23 mm
- **Internal width :** 23 mm

### RADNABE

- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Axle material :** aluminum
- **Axle material :** aluminum
- **Axle material :** aluminum
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible

Nabe nur fÃ¼r Center-LockÂ®-Bremsscheiben erhÃ¤ltlich

Instant Drive 360

Instant Drive 360

Instant Drive 360

QRM Auto

### RADGEWICHTE

775

Download date: 2024-03-29 / Update date: 2024-02-15