
# Cosmic SLR 45 Disc




ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included
Recommended tyre sizes: 25 to 32 mm
Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the 2

## REFERENZEN RÃ¤DER

| | |
|---|---|
| F90181 | Cosmic SLR 45 DCL Ft |




## RIMS



 :

| | | |
|---|---|---|
| 1 | V4095015 | Kit Front/Rear rim Cosmic SLR 45 Disc MY22 |
| 1 | V4093615 | Kit Front/Rear rim Cosmic SLR 45 Disc - while stock last |

## SPOKES

| | | |
|---|---|---|
| 2 | V4163701 | Kit 12 Front/Rear Cosmic SLR 45 Disc aero stainless spoke 27 |

## HUB SHELLS

| | | |
|---|---|---|
| 3 | N/A | NABENKÖRPER |
| 3 | N/A | NABENKÖRPER |
| 4 | M40129 | KIT 2 BEARINGS 6902 15x28x7 |
| 5 | V2373301 | KIT QRM AUTO FRONT AXLE 12mm > 2019 |

## ADAPTERS

| | | |
|---|---|---|
| 6 | V2374701 | KIT FRONT ROAD FORK REST 12mm FOR J BENT DISC HUB |
| | V2680301 | "Kit Ft Road Adapter 12 >> 9mm" |

Download date: 2024-03-28 / Update date: 2024-03-13

# MAVIC Cosmic SLR 45 Disc



## GELIEFERT MIT

| | |
|---|---|
| UST valve and accessories (129 838 01) | |
| User guide | |

## COMPATIBILITY

| | |
|---|---|
| Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies | |
| VR-Achse: 12-mm-Steckachse, mit optionalen Adaptern einfach auf Schnellspanner umrÃ¼stbar. Nicht umrÃ¼stbar auf 15-mm-Steckachse. | |
| Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters | |

## Specifications

### FELGEN

- **Material :** 100% carbon fiber
- **Height :** 45 mm

Disc brake specific profile

- **Tire :** UST Tubeless and tubetype
- **Internal width :** 19 mm
- **ETRTO size :** 622x19TC Road

Fore Carbon
UST

### SPEICHEN

- **Material :** steel
- **Shape :** straight pull, elliptical aero, double butted (patented)
- **Nipples :** Fore integrated aluminum
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless

### RADNABE

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum
- **Front :** Quick release and 12x100 through axle compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible

Infinity Hub
Instant Drive 360
QRM Auto

### VERSIONS

- **Disc standard :** Center Lock (R) only
- **Freewheel :** Shimano/Sram or XD-Road

### RADGEWICHTE

670

Download date: 2024-03-28 / Update date: 2024-03-13