


ASTM CATEGORY 2 : road and offroad with jumps less than 15cm  
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included  
Maximum tyre pressure: 4.6bar/67PSI with a 28mm tyre - 32.7bar/39PSI with a 64mm tyre  
Recommended tyre sizes: 28 to 64 mm (1.1" to 2.5")  
Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the 2

## REFERENCES WHEELS

F90221 ALLROAD S CL 700 12X100



## RIMS



&NBSP::

1	V00097531	Kit Front/Rear rim Allroad S 23
1	V4092115	Kit Front/Rear rim Allroad S while stock lasts

## SPOKES

2	V4162601	Kit 12 Front/Rear Allroad S flat spoke 298 M7/7
---	----------	---

## HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2374001	KIT 12x100mm FRONT AXLE DCL QRM AUTO ALLROAD > 2019

## OPTIONS

6	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	V2680301	"Kit Ft Road Adapter 12 >> 9mm"
	V2373501	QRM Auto front axle 15mm for DCL Allroad wheels > 2019



# ALLROAD S DISC

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Front axle: 12mm thru axle, easily convertible to quick release with optional adapters. Convertible to 15mm with complete axle replacement	
Front axle: 12mm thru axle, easily convertible to quick release with optional adapters. Convertible to 15mm with complete axle replacement	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- Material : Mxstal
  - Material : Mxstal
  - Height : 22 mm
  - Height : 22 mm
- SUP
- Disc brake specific profile
- Disc brake specific profile
- Tire : UST Tubeless and tubetype
  - Tire : UST Tubeless and tubetype
  - Internal width : 22 mm
  - Internal width : 22 mm
  - ETRTO size : 622x22TSS ROAD
  - ETRTO size : 622x22TSS ROAD
- Hookless profile
- Hookless profile
- Fore
- Fore
- UST
- UST
- SUP

SPOKES

- Material : steel
- Material : steel
- Shape : straight pull, flat, double butted
- Shape : straight pull, flat, double butted
- Nipples : Fore integrated aluminum
- Nipples : Fore integrated aluminum
- Count : 24 front and rear
- Count : 24 front and rear
- Lacing : front and rear crossed 2, contactless
- Lacing : front and rear crossed 2, contactless

WHEEL HUB

- Infinity Hub
- Front and rear bodies : aluminum
  - Axle material : aluminum
- Instant Drive 360
- QRM Auto
- Front : Quick release, 12x100 and 15x100 through axle compatible
  - Front and rear bodies : aluminum
  - Rear : Quick Release, 12x142 and 12x135 compatible
  - Axle material : aluminum
- Hub available for Center Lock brake rotors only
- Front : Quick release, 12x100 and 15x100 through axle compatible
  - Rear : Quick Release, 12x142 and 12x135 compatible
- Infinity Hub
- Instant Drive 360
- QRM Auto

VERSIONS

- Disc standard : Center Lock (R) only
- Disc standard : Center Lock (R) only
- Freewheel : Shimano/Sram
- Freewheel : Shimano/Sram or XD-Road

WHEEL WEIGHTS

830