
MAVIC ALLROAD SL DISC

2021
FRONT

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included
Maximum tyre pressure: 4.6bar/67PSI with a 28mm tyre - 32.7bar/39PSI with a 64mm tyre
Recommended tyre sizes: 28 to 64 mm (1.1" to 2.5")
Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the 2

REFERENCES WHEELS

F90331	ALL SL CL 700 12X100



RIMS



 :

1	V00097431	Kit Front/Rear rim Allroad SL 23
1	V4092015	Kit Front/Rear rim Allroad SL while stock lasts

SPOKES

2	V4162501	Kit 12 Front/Rear Allroad SL aero spoke 298 M7/7

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2374001	KIT 12x100mm FRONT AXLE DCL QRM AUTO ALLROAD > 2019

OPTIONS

	V2680301	"Kit Ft Road Adapter 12 >> 9mm"
	V2373501	QRM Auto front axle 15mm for DCL Allroad wheels > 2019
	V2372501	15mm MTB Axle Cap QRM Auto From 2019

Download date: 2024-03-28 / Update date: 2024-03-13

MAVIC ALLROAD SL DISC

2021
FRONT

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Front axle: 12mm thru axle, easily convertible to quick release with optional adapters. Convertible to 15mm with complete axle replacement	
Front axle: 12mm thru axle, easily convertible to quick release with optional adapters. Convertible to 15mm with complete axle replacement	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Height :** 22 mm
- **Height :** 22 mm

SUP
Disc brake specific profile
Disc brake specific profile

- **Weight reduction :** ISM 4D
- **Weight reduction :** ISM 4D
- **Tire :** UST Tubeless and tubetype
- **Tire :** UST Tubeless and tubetype
- **Internal width :** 22 mm
- **Internal width :** 22 mm
- **ETRTO size :** 622x22TSS ROAD
- **ETRTO size :** 622x22TSS ROAD

Hookless profile
Hookless profile
Fore
Fore
UST
UST
SUP

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** straight pull, elliptical aero, double butted (patented)
- **Shape :** straight pull, elliptical aero, double butted (patented)
- **Nipples :** Fore integrated aluminum
- **Nipples :** Fore integrated aluminum
- **Count :** 24 front and rear
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless
- **Lacing :** front and rear crossed 2, contactless

WHEEL HUB

Infinity Hub

- **Front and rear bodies :** aluminum
- **Axle material :** aluminum

Instant Drive 360
QRM Auto

- **Front and rear bodies :** aluminum
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Axle material :** aluminum
- **Rear :** Quick Release, 12x142 and 12x135 compatible

Hub available for Center Lock brake rotors only

- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible

Infinity Hub
Instant Drive 360
QRM Auto

VERSIONS

- **Disc standard :** Center Lock (R) only
- **Disc standard :** Center Lock (R) only
- **Freewheel :** Shimano/Sram or XD-Road
- **Freewheel :** Shimano/Sram

WHEEL WEIGHTS

740

Download date: 2024-03-28 / Update date: 2024-03-13