
MAVIC ALLROAD SL DISC

2021
REAR

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included
Recommended tyre sizes: 28 to 64 mm (1.1" to 2.5")
Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the 2
Maximum tyre pressure: 4.6bar/67PSI with a 28mm tyre - 32.7bar/39PSI with a 64mm tyre

REFERENZEN RÃ¤DER

R36881	ALL SL CL 700 12X142 M11	R39131	ALL SL CL 700 12X142 XDR



RIMS

 :

1	V00097431	Kit Front/Rear rim Allroad SL 23
1	V4092015	Kit Front/Rear rim Allroad SL while stock lasts

SPOKES

2	V4162501	Kit 12 Front/Rear Allroad SL aero spoke 298 M7/7

HUB SHELLS

3	N/A	NABENKÖRPER
3	N/A	NABENKÖRPER
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V00046431	KIT AXE ID360 142LIGHT CL+ClR
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V00063631	Kit ID360 seal version 2 (larger)
8	V2251701	ID360 2 RATCHETS + SPRING + GREASE
9	V2500501	Kit 3 ID360 pad for noise reduction
10	V2251801	KIT 3 ID360 ROAD SPRINGS
11	V2580101	FREEHUB BODY XD Road ID360
11	V3430101	HG11 Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing

OPTIONS

	V2510801	ID360 EVO REAR AXLE ADAPTERS 9x135mm DCL & D6T
	V2510901	ID360 EVO REAR AXLE ADAPTERS 12x135mm DCL & D6T
	V2373401	KIT ID360 135/142 DCL L1 AXLE WITH CLIP
	V2510701	ID360 EVO REAR AXLE ADAPTERS 12x142mm DCL & D6T

ADAPTERS

13	V3811001	KIT ROAD ID360 RR CL ENDCAP (12MM)

Download date: 2024-03-28 / Update date: 2024-03-13

MAVIC ALLROAD SL DISC

GELIEFERT MIT

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
MultifunktionsÃ¯Â¿Â½ssel (325 423 01)	
User guide	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
Freewheel: Shimano/Sram, convertible to Campagnolo and XD-R with optional driver bodies	
VR-Achse: 12-mm-Steckachse, mit optionalen Adaptern einfach auf Schnellspanner umrÃ¯Â¿Â½stbar. UmrÃ¯Â¿Â½stung auf 15-mm-Steckachse durch Austausch der komplet	
VR-Achse: 12x100 mm, umrÃ¯Â¿Â½stbar auf Schnellspanner (mit beiliegenden Adaptern). UmrÃ¯Â¿Â½stung auf 15x100 mm durch Austausch der kompletten Achse mÃ¶glich	
VR-Achse: 12x100 mm, umrÃ¯Â¿Â½stbar auf Schnellspanner (mit beiliegenden Adaptern). UmrÃ¯Â¿Â½stung auf 15x100 mm durch Austausch der kompletten Achse mÃ¶glich	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	
Rear axle: 12mm thru axle, convertible to Quick Release with optional adapters	

Specifications

FELGEN

- **Material :** Maxtal
- **Height :** 22 mm

Disc brake specific profile

- **Weight reduction :** ISM 4D
- **Material :** Maxtal
- **Material :** Maxtal
- **Tire :** UST Tubeless and tubetype
- **Height :** 22 mm
- **Height :** 22 mm
- **Internal width :** 22 mm
- **ETRTO size :** 622x22TSS ROAD

Hookless profile
Disc brake specific profile
Disc brake specific profile

- **Weight reduction :** ISM 4D
- **Weight reduction :** ISM 4D
- **Tire :** UST Tubeless and tubetype
- **Tire :** UST Tubeless and tubetype
- **Internal width :** 22 mm
- **Internal width :** 22 mm
- **ETRTO size :** 622x22TSS ROAD
- **ETRTO size :** 622x22TSS ROAD

Hookless profile
Hookless profile
Fore
Fore
Fore
UST
UST
UST
SUP
SUP
SUP

SPEICHEN

RADNABE

- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Front and rear bodies :** aluminum
- **Axle material :** aluminum
- **Axle material :** aluminum
- **Axle material :** aluminum

Infinity Hub

- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible
- **Rear :** Quick Release, 12x142 and 12x135 compatible

Infinity Hub
Infinity Hub
Nabe nur fÃ¼r Center-LockÂ®-Bremsscheiben erhÃ¤ltlich
Instant Drive 360
Instant Drive 360
Instant Drive 360
QRM Auto
QRM Auto
QRM Auto

VERSIONS

- **Disc standard :** Center Lock (R) only
- **Disc standard :** Center Lock (R) only
- **Disc standard :** Center Lock (R) only
- **Freewheel :** Shimano/Sram or XD-Road

RADGEWICHTE

850

Download date: 2024-03-28 / Update date: 2024-03-13