

ASTM CATEGORY 3 : CROSS COUNTRY

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included

Maximum tyre pressure: 4.1bar/59PSI with a 28mm tyre - 2.45bar/36PSI with a 64mm tyre



Recommended tyre sizes: 28 to 64 mm (1.1" to 2.5")

Recommended tyre sizes: 50mm to 76mm (2.0" to 3.0")

REFERENCES WHEELS

F90452 XMAX SL INT 29 BST

F91952 XMAX SL CL 29 BST



RIMS



&NBSP;;

1 V3765715 Kit Front/Rear rim Crossmax SL 21 29"

SPOKES

2 V2388301 Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29" butted spoke 2

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL
6	N/A	HUB BODY
7	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019

OPTIONS

V2374401

TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8	V2372501 99694101	15mm MTB Axle Cap QRM Auto From 2019 ADAPTER Ft 15 to 9mm QR
---	----------------------	---



CROSSMAX SL 29

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
Fore adjustment wrench	
Fore adjustment wrench	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separately)	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- Material : Mxtal
- Material : Mxtal
- Material : Mxtal
- Material : S6000 Aluminum
- Material : S6000 Aluminum
- Height : 22 mm
- SUP
- SUP
- Internal width : 25 mm
- Fore
- Tire : UST Tubeless and tubetype
- Tire : UST Tubeless and tubetype
- Internal width : 25 mm
- Internal width : 25 mm
- Disc brake specific profile
- E-Bike specific rim profile
- ETRTO size 29" : 622x25TSS
- ETRTO size 29" : 622x25TSS
- Hookless profile
- Hookless profile
- ETRTO size 29" : 622x25TSS
- Black Shield treatment (protects your rim against impacts and scratches)
- Black Shield treatment (protects your rim against impacts and scratches)

WHEEL HUB

- Infinity Hub
- Body : aluminum
- Instant Drive 360
- Axles : Front 15X110 Boost ; Rear 12X148 Boost
- Hub available with 6-bolt or center lock (R) brake rotors
- Body design : INFINITY
 - Disc standard : 6 Bolts or Center Lock®
 - Axle material : aluminum
 - Rear body : aluminum
 - Axles : Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
 - Freewheel : Shimano HG MTB / Shimano MS / Sram XD MTB
 - Freewheel : FTS-L steel
- Infinity Hub
- 24 teeth ratchet
- Hub available with 6-bolt or center lock (R) brake rotors
- Axles : Front 15X110 Boost ; Rear 12X148 Boost
- Instant Drive 360

VERSIONS

- Disc standard : 6 Bolts or Center Lock (R)
- Disc standard : 6 Bolts or Center Lock (R)

WHEEL WEIGHTS

785