

MAVIC Crossmax SL Ultimate 25 29

ASTM CATEGORY 3 : CROSS COUNTRY
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Recommended tyre sizes: 50mm to 76mm (2.0" to 3.0")

REFERENZEN RÃ¤DER

F90422	Xmax SL Ulti 25 29 DCL Ft Bst*	F92242	Xmax SL Ulti25 29 INTL Ft Bst*





RIMS



 :

1	V3766615	Kit Front/Rear rim Crossmax SL Ultimate 25 -while stock last
1	V2700101	UST Tape 28mm for 25 to 27mm wide rims
	V00004831	Kit Front/Rear rim Crossmax SL Ultimate 29'' 22

SPOKES

2	V00065231	Kit 12 Front/Rear Crossmax SL Ultimate 29'' butted stainless
2	V2389101	Kit 12Fr/Rr XmaxSL Ultimate spk293+np&w while stock last

HUB SHELLS

3	N/A	NABENKÖRPER
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL
6	N/A	NABENKÖRPER
7	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019

OPTIONS

	V2374401	TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8	V2372501	KIT FT MTB FORKREST FROM 2019
	99694101	2 REDUCERS 15/9mm

Download date: 2024-03-28 / Update date: 2023-09-13

MAVIC Crossmax SL Ultimate 25 29

GELIEFERT MIT

UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Wheelbag (V24 801 01)	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	

Specifications

FELGEN

- **Material :** 100% carbon fiber
- **Drilling :** traditional
- **Internal width :** 25 mm
- **ETRTO size 29" :** 622x25TSS

Hookless profile
Asymmetrical rim design
Adaptive Layup Carbon technology
UST Tubeless Ready

SPEICHEN

- **Material :** steel
- **Shape :** straight pull, flat, double butted
- **Nipples :** aluminum, ABS
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless

RADNABE

Infinity Hub
24 teeth ratchet
Hub available with 6-bolt or center lock (R) brake rotors

- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost

Instant Drive 360
QRM Auto

VERSIONS

- **Disc standard :** 6 Bolts or Center Lock (R)
- **Hub width :** Boost only (front 110, rear 148)
- **Freewheel :** SRAM XD, Shimano HG9, Shimano Micro-Spline

RADGEWICHTE

605

Download date: 2024-03-28 / Update date: 2023-09-13