
# MAVIC Crossmax SL Ultimate 25 29

ASTM CATEGORY 3 : CROSS COUNTRY
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Recommended tyre sizes: 50mm to 76mm (2.0" to 3.0")

## REFERENZEN RÃ¤DER

| | | | |
|---|---|---|---|
| R37713 | Xmax SL Ulti 25 29DCL RrBstMS* | R39952 | Xmax SL Ulti25 29INTL Rr Bst* |
| R39752 | Xmax SL Ulti25 29INTL RrBstXD* | | |




## RIMS

 :

| | | |
|---|---|---|
| 1 | V00004831 | Kit Front/Rear rim Crossmax SL Ultimate 29'' 22 |
| 1 | V3766615 | Kit Front/Rear rim Crossmax SL Ultimate 25 -while stock last |
| | V2700101 | UST Tape 28mm for 25 to 27mm wide rims |

## SPOKES

| | | |
|---|---|---|
| 2 | V00065231 | Kit 12 Front/Rear Crossmax SL Ultimate 29'' butted stainless |
| 2 | V2389101 | Kit 12Fr/Rr XmaxSL Ultimate spk293+np&w while stock last |

## HUB SHELLS

| | | |
|---|---|---|
| 3 | N/A | NABENKÖRPER |
| 4 | M40076 | HUB BEARINGS 17x30x7 6903 x 2 |
| 5 | V2375701 | Kit ID360 148 DCL axle with circlip |
| 6 | V2252701 | KIT ID360 INSERT SHAPED EAR LOBE > 2017 |
| 7 | V00063631 | Kit ID360 seal version 2 (larger) |
| 8 | V2375201 | KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific) |
| 9 | V2375401 | KIT ID360 MTB 24T 3 NOISE REDUCING PADS |
| 10 | V2372901 | KIT 3 ID360 MTB SPRINGS |
| 11 | V3990101 | MicroSpline MTB Freewheel Body ID360 |
| 11 | V3780101 | HG9 Alloy MTB Freewheel Body ID360 |
| 11 | V3740101 | XD MTB Freewheel Body ID360 |
| 12 | V2373001 | KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing |
| 13 | N/A | NABENKÖRPER |
| 14 | V2372201 | KIT ID360 148 D6T AXLE WITH CLIP |

## OPTIONS

| | | |
|---|---|---|
| | V2372801 | KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD |

## ADAPTERS

| | | |
|---|---|---|
| 15 | V2510701 | ID360 EVO REAR AXLE ADAPTERS 12x142mm DCL & D6T |
| | V2510801 | ID360 EVO REAR AXLE ADAPTERS 9x135mm DCL & D6T |

Download date: 2024-03-29 / Update date: 2023-09-13

# MAVIC Crossmax SL Ultimate 25 29

## GELIEFERT MIT

| | |
|---|---|
| UST valve and accessories (129 838 01) | |
| Pre-installed tubeless rim tape | |
| Multifonction adjustment wrench (delivered with rear wheel) (325 423 01) | |
| Wheelbag (V24 801 01) | |
| 2 replacement spokes with each wheel | |

## COMPATIBILITY

| | |
|---|---|
| Freewheel: Shimano HG9, XD or Micro Spline | |
| Rear axle: 12x148 Boost thru axle | |
| Front axle: 15x110 Boost thru axle | |

## Specifications

### FELGEN

- **Material :** 100% carbon fiber
- **Drilling :** traditional
- **Internal width :** 25 mm
- **ETRTO size 29" :** 622x25TSS

Hookless profile
Asymmetrical rim design
Adaptive Layup Carbon technology
UST Tubeless Ready

### SPEICHEN

- **Material :** steel
- **Shape :** straight pull, flat, double butted
- **Nipples :** aluminum, ABS
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless

### RADNABE

Hub available with 6-bolt or center lock (R) brake rotors

- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost

Infinity Hub
24 teeth ratchet
Instant Drive 360
QRM Auto

### VERSIONS

- **Disc standard :** 6 Bolts or Center Lock (R)
- **Hub width :** Boost only (front 110, rear 148)
- **Freewheel :** SRAM XD, Shimano HG9, Shimano Micro-Spline

### RADGEWICHTE

735

Download date: 2024-03-29 / Update date: 2023-09-13