

MAVIC CROSSMAX SL S 29

ASTM CATEGORY 3 : CROSS COUNTRY
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Maximum tyre pressure: 4.1bar/59PSI with a 28mm tyre - 2.45bar/36PSI with a 64mm tyre
Recommended tire sizes: 28 to 64 mm (1.1" to 2.5")
Recommended tyre sizes: 50mm to 76mm (2.0" to 3.0")

REFERENCES WHEELS

F90443	XMAX SLS INT 29 BST	F91963	XMAX SLS CL 29 BST





RIMS



 :

1	V3765815	Kit Front/Rear rim Crossmax SLS 29''

SPOKES

2	V2388301	Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29'' butted spoke 2

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL
6	N/A	HUB BODY
7	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019

OPTIONS

	V2374401	TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	99694101	ADAPTER Ft 15 to 9mm QR

Download date: 2024-03-28 / Update date: 2024-02-15

MAVIC CROSSMAX SL S 29

2021
FRONT

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	
Fore adjustment wrench	
Fore adjustment wrench	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Material :** Maxtal
- **Material :** S6000 Aluminum
- **Material :** S6000 Aluminum
- **Height :** 22 mm

SUP
SUP

- **Internal width :** 25 mm
- **Weight reduction :** ISM 4D
- **Weight reduction :** ISM 4D

Fore

- **Tire :** UST Tubeless and tubetype
- **Tire :** UST Tubeless and tubetype
- **Internal width :** 25 mm
- **Internal width :** 25 mm

Disc brake specific profile
E-Bike specific rim profile

- **ETRTO size 29" :** 622x25TSS
- **ETRTO size 29" :** 622x25TSS

Hookless profile
Hookless profile

- **ETRTO size 29" :** 622x25TSS

Black Shield treatment (protects your rim against

WHEEL HUB

- **Body :** aluminum

Infinity Hub
Instant Drive 360
Hub available with 6-bolt or center lock (R) brake rotors

- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost
- **Body design :** INFINITY
- **Disc standard :** 6 Bolts or Center LockÂ®
- **Axle material :** aluminum
- **Rear body :** aluminum
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Freewheel :** Shimano HG MTB / Shimano MS / Sram XD MTB
- **Freewheel :** FTS-L steel

Hub available with 6-bolt or center lock (R) brake rotors

- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost

Infinity Hub
24 teeth ratchet
Instant Drive 360

VERSIONS

- **Disc standard :** 6 Bolts or Center Lock (R)

WHEEL WEIGHTS

745

Downloaded on 2024-02-15 · Retrieved date: 2024-02-15