

ASTM CATEGORY 3 : CROSS COUNTRY

Maximum tyre pressure: 4.1bar/59PSI with a 28mm tyre - 2.45bar/36PSI with a 64mm tyre

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included


Recommended tyre sizes: 28 to 64 mm (1.1" to 2.5")

Recommended tyre sizes: 50mm to 76mm (2.0" to 3.0")

REFERENCES WHEELS

R37032	XMAX SLS INT 29 BST HG
R37733	XMAX SLS INT 29 BST XD

R39153	XMAX SLS CL 29 BST MS
--------	-----------------------



RIMS



&NBSP;:

1	V3765815	Kit Front/Rear rim Crossmax SLS 29"
---	----------	-------------------------------------

SPOKES

2	V2388301	Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29" butted spoke 2
---	----------	---

HUB SHELLS

3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2375701	Kit ID360 148 DCL axle with circlip
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V00063631	Kit ID360 seal version 2 (larger)
8	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
9	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
10	V2372901	KIT 3 ID360 MTB SPRINGS
11	V3990101	MicroSpline MTB Freewheel Body ID360
11	V3780101	HG9 Alloy MTB Freewheel Body ID360
11	V3740101	XD MTB Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
13	N/A	HUB BODY
14	V2372201	KIT ID360 148 D6T AXLE WITH CLIP

OPTIONS

8	V2372801	KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD
---	----------	---

ADAPTERS

15	V2510701	ID360V2RrAxleAdapt12x142/148
	V2510801	ID360 V2 RrAxleAdapt9x135

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	
Fore adjustment wrench	
Fore adjustment wrench	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separately)	
Front axle: 15x110 Boost thru axle	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- Material : Mxstal
- Material : Mxstal
- Material : Mxstal
- Material : S6000 Aluminum
- Material : S6000 Aluminum
- Height : 22 mm
- SUP
- SUP
- Internal width : 25 mm
- Weight reduction : ISM 4D
- Weight reduction : ISM 4D
- Fore
- Tire : UST Tubeless and tubetype
- Tire : UST Tubeless and tubetype
- Internal width : 25 mm
- Internal width : 25 mm
- Disc brake specific profile
- E-Bike specific rim profile
- ETRTO size 29" : 622x25TSS
- ETRTO size 29" : 622x25TSS
- Hookless profile
- Hookless profile
- ETRTO size 29" : 622x25TSS date: 2024-04-10
- Asymmetrical rim design

WHEEL HUB

- Infinity Hub
- Body : aluminum
- Instant Drive 360
- Hub available with 6-bolt or center lock (R) brake rotors
- Axles : Front 15X110 Boost ; Rear 12X148 Boost
 - Body design : INFINITY
 - Disc standard : 6 Bolts or Center Lock®
 - Axle material : aluminum
 - Rear body : aluminum
 - Axles : Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
 - Freewheel : Shimano HG MTB / Shimano MS / Sram XD MTB
 - Freewheel : FTS-L steel
 - Axles : Front 15X110 Boost ; Rear 12X148 Boost
- Infinity Hub
- 24 teeth ratchet
- Hub available with 6-bolt or center lock (R) brake rotors
- Instant Drive 360

VERSIONS

- Disc standard : 6 Bolts or Center Lock (R)
- Disc standard : 6 Bolts or Center Lock (R)

WHEEL WEIGHTS

870