

MAVIC CROSSMAX XL S 29

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Recommended tyre sizes: 60mm to 76mm (2.35" to 3.0")
Maximum tyre pressure: 2.95bar/43PSI with a 52mm tyre - 1.55bar/22PSI with a 125mm tyre
MindestgrÃ¶Ã?e des Reifens: Breite 52mm - max. Druck 2.95Bar/43PSI

REFERENZEN RÃ¤DER

F90493	XMAX XLS INT 29 BST	F91972	XMAX XLS CL 29 BST





RIMS



 :

1	V3765915	Kit Front/Rear rim Crossmax XLS 29''

SPOKES

2	V2388301	Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29'' butted spoke 2

HUB SHELLS

3	N/A	NABENKÖRPER
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL
6	N/A	NABENKÖRPER
7	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019

OPTIONS

	V2374401	TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	99694101	2 REDUCERS 15/9mm

Download date: 2024-03-28 / Update date: 2024-02-15

MAVIC CROSSMAX XL S 29

GELIEFERT MIT

2 replacement spokes with each wheel	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Bedienungsanleitung	
2 replacement spokes with each wheel	
Fore adjustment wrench	
Fore adjustment wrench	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel: Shimano HG9, XD or Micro Spline	
Front axle: 15x110 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
FreilaufkÃ¶rper: SHIMANO HG MTB Stahl-konverter (Kit V3790101 separat erhÃ¤ltlich)	
Adapter Hinterachse: 12x148 umwandelbar in 9x141 (Kit V2510801 separat erhÃ¤ltlich)	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
VR-Achse: nur fÃ¼r Schraubmuttern (im Lieferumfang enthalten), M10x1-Gewinde	

Specifications

FELGEN

- **Material :** Maxtal
- **Material :** S6000 Aluminum
- **Material :** Maxtal
- **Weight reduction :** ISM
- **Material :** Maxtal
- **Material :** Maxtal
- **Material :** S6000 Aluminum
- **Tire :** UST Tubeless and tubetype
- **Material :** S6000 Aluminum
- **Internal width :** 30 mm

RADNABE

- **KÃ¶rpermaterial :** aluminium

Infinity Hub

- **KÃ¶rperdesign :** INFINITY
- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost
- **Standard Disc :** 6 LÃ¶cher oder Center LockÂ®

Hub available with 6-bolt or center lock (R) brake rotors

- **Material der Achse :** Aluminium
- **AchsgrÃ¶Ãe :** vorne 15x110 / hinten 12x148
- **Freilauftechnologie :** Instant Drive 360

RADGEWICHTE

830

Download date: 2024-03-28 / Update date: 2024-02-15