

MAVIC CROSSMAX XL S 29

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Maximum tyre pressure: 2.95bar/43PSI with a 52mm tyre - 1.55bar/22PSI with a 125mm tyre
Minimum tyre size: width 52mm - pressure max. 2.95Bar/43PSI
Recommended tyre sizes: 60mm to 76mm (2.35" to 3.0")

REFERENCES WHEELS

F90493	XMAX XLS INT 29 BST	F91972	XMAX XLS CL 29 BST





RIMS



 :

1	V3765915	Kit Front/Rear rim Crossmax XLS 29''

SPOKES

2	V2388301	Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29'' butted spoke 2

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL
6	N/A	HUB BODY
7	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019

OPTIONS

	V2374401	TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	99694101	ADAPTER Ft 15 to 9mm QR

Download date: 2024-03-28 / Update date: 2024-02-15

MAVIC CROSSMAX XL S 29

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
Fore adjustment wrench	
Fore adjustment wrench	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- **Material :** Maxtal
- **Material :** Maxtal
- **Material :** Maxtal
- **Material :** S6000 Aluminum
- **Material :** S6000 Aluminum
- **Height :** 22 mm

SUP

SUP

- **Internal width :** 30 mm
- **Weight reduction :** ISM
- **Weight reduction :** ISM

Fore

- **Tire :** UST Tubeless and tubetype
- **Tire :** UST Tubeless and tubetype

Disc brake specific profile

- **Internal width :** 30 mm
- **Internal width :** 30 mm

Asymmetrical rim design

- **ETRTO size 29" :** 622x30TC

Black Shield treatment (protects your rim against impacts and scratches)

Black Shield treatment (protects your rim against impacts and scratches)

- **ETRTO size 29" :** 622x30TC

WHEEL HUB

Infinity Hub

- **Body :** aluminum

Instant Drive 360

QRM Auto

Hub available with 6-bolt or center lock (R) brake rotors

- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost
- **Body design :** INFINITY
- **Disc standard :** 6 Bolts or Center LockÂ®
- **Axle material :** aluminum
- **Rear body :** aluminum
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Freewheel :** Shimano HG MTB / Shimano MS / Sram XD MTB
- **Freewheel :** FTS-L steel
- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost

Infinity Hub

24 teeth ratchet

Hub available with 6-bolt or center lock (R) brake rotors

Instant Drive 360

QRM Auto

VERSIONS

WHEEL WEIGHTS

830

Downloaded from BCS / Update date: 2024-02-15