

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING

Maximum tyre pressure: 2.95bar/43PSI with a 52mm tyre - 1.55bar/22PSI with a 125mm tyre

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included


Minimum tyre size: width 52mm - pressure max. 2.95Bar/43PSI

Recommended tyre sizes: 60mm to 76mm (2.35" to 3.0")

REFERENCES WHEELS

R37083 XMAX XLS INT 29 BST HG
R37773 XMAX XLS INT 29 BST XD

R39163 XMAX XLS CL 29 BST MS



RIMS



&NBSP;:

1 V3765915 Kit Front/Rear rim Crossmax XLS 29"

SPOKES

2 V2388301 Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29" butted spoke 2

HUB SHELLS

3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2375701	Kit ID360 148 DCL axle with circlip
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V00063631	Kit ID360 seal version 2 (larger)
8	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
9	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
10	V2372901	KIT 3 ID360 MTB SPRINGS
11	V3990101	MicroSpline MTB Freewheel Body ID360
11	V3780101	HG9 Alloy MTB Freewheel Body ID360
11	V3740101	XD MTB Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
13	N/A	HUB BODY
14	V2372201	KIT ID360 148 D6T AXLE WITH CLIP

OPTIONS

8 V2372801 KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD

ADAPTERS

15 V2510701 ID360V2RrAxleAdapt12x142/148
V2510801 ID360 V2 RrAxleAdapt9x135



CROSSMAX XL S 29

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
2 replacement spokes with each wheel	
Fore adjustment wrench	
Fore adjustment wrench	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separately)	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- Material : Mxtal
- Material : Mxtal
- Material : Mxtal
- Material : S6000 Aluminum
- Material : S6000 Aluminum
- Height : 22 mm
- SUP
- SUP
- Internal width : 30 mm
- Weight reduction : ISM
- Weight reduction : ISM
- Fore
- Tire : UST Tubeless and tubetype
- Tire : UST Tubeless and tubetype
- Disc brake specific profile
- Internal width : 30 mm
- Internal width : 30 mm
- Asymmetrical rim design
- ETRTO size 29" : 622x30TC
- Black Shield treatment (protects your rim against impacts and scratches)
- Black Shield treatment (protects your rim against impacts and scratches)
- ETRTO size 29" : 622x30TC
- ETRTO size 29" : 622x30TC

WHEEL HUB

- Infinity Hub
- Body : aluminum
- Instant Drive 360
- QRM Auto
- Hub available with 6-bolt or center lock (R) brake rotors
- Axles : Front 15X110 Boost ; Rear 12X148 Boost
 - Body design : INFINITY
 - Disc standard : 6 Bolts or Center Lock®
 - Axle material : aluminum
 - Rear body : aluminum
 - Axles : Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
 - Freewheel : Shimano HG MTB / Shimano MS / Sram XD MTB
 - Freewheel : FTS-L steel
- Hub available with 6-bolt or center lock (R) brake rotors
- Axles : Front 15X110 Boost ; Rear 12X148 Boost
- Infinity Hub
- 24 teeth ratchet
- Instant Drive 360
- QRM Auto
- VERSIONS

WHEEL WEIGHTS

960