
MAVIC CROSSMAX XL S 29

2021
REAR

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Recommended tyre sizes: 60mm to 76mm (2.35" to 3.0")
Maximum tyre pressure: 2.95bar/43PSI with a 52mm tyre - 1.55bar/22PSI with a 125mm tyre
TamaÃ±o mÃnimo del neumÃ¡tico: anchura 52 mm - presiÃ³n mÃ¡x. 2,95 bar/43 psi

RUEDAS REFERENCIAS

R37083	XMAX XLS INT 29 BST HG	R39163	XMAX XLS CL 29 BST MS
R37773	XMAX XLS INT 29 BST XD		



RIMS



 :

1	V3765915	Kit Front/Rear rim Crossmax XLS 29''

SPOKES

2	V2388301	Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29'' butted spoke 2

HUB SHELLS

3	N/A	CUERPO DE BUJE
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2375701	Kit ID360 148 DCL axle with circlip
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V00063631	Kit ID360 seal version 2 (larger)
8	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
9	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
10	V2372901	KIT 3 ID360 MTB SPRINGS
11	V3990101	MicroSpline MTB Freewheel Body ID360
11	V3780101	HG9 Alloy MTB Freewheel Body ID360
11	V3740101	XD MTB Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
13	N/A	CUERPO DE BUJE
14	V2372201	KIT ID360 148 D6T AXLE WITH CLIP

OPTIONS

8	V2372801	KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD

ADAPTERS

15	V2510701	ID360 EVO REAR AXLE ADAPTERS 12x142mm DCL & D6T
	V2510801	ID360 EVO REAR AXLE ADAPTERS 9x135mm DCL & D6T

Download date: 2024-03-29 / Update date: 2024-02-15

MAVIC CROSSMAX XL S 29

ENTREGADO CON

2 replacement spokes with each wheel	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
GuÃa del usuario	
2 replacement spokes with each wheel	
Fore adjustment wrench	
Fore adjustment wrench	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel: Shimano HG9, XD or Micro Spline	
Front axle: 15x110 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Cuerpo de rueda libre: convertible SHIMANO HG MTB acero (kit V3790101 vendido por separado)	
Adaptadores eje trasero: 12x148 convertible a 9x141 (kit V2510801 vendido por separado)	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Eje delantero: solo para tuercas de fijaciÃ³n (incluidas), rosca M9x1	

Specifications

LLANTAS

- **Material :** Maxtal
- **Material :** S6000 Aluminum
- **Material :** Maxtal
- **Weight reduction :** ISM
- **Material :** Maxtal
- **Material :** Maxtal
- **Material :** S6000 Aluminum
- **Tire :** UST Tubeless and tubetype
- **Material :** S6000 Aluminum
- **Internal width :** 30 mm

BUJE DE LA RUEDA

- **Material del cuerpo :** aluminio

Infinity Hub

- **DiseÃ±o del cuerpo :** INFINITY
- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost
- **Disco estÃ¡ndar :** sÃ³lo 6 orificios o Center Lock

Hub available with 6-bolt or center lock (R) brake rotors

- **Material del eje :** aluminio
- **TamaÃ±o del eje :** delantero 15x110 / trasero 12x148

PESOS DE RUEDAS

960

Download date: 2024-03-29 / Update date: 2024-02-15