

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING

Maximum tyre pressure: 2.95bar/43PSI with a 52mm tyre - 1.55bar/22PSI with a 125mm tyre

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included


Minimum tyre size: width 52mm - pressure max. 2.95Bar/43PSI

Recommended tyre sizes: 60mm to 76mm (2.35" to 3.0")

REFERENCES WHEELS

F90512 XMAX XL INT 29 BST

F91982 XMAX XL CL 29 BST



RIMS



&NBSP;:

1 V3766015 Kit Front/Rear rim Crossmax XL 29" MY21

SPOKES

2 V2388301 Kit 12 Front/Rear Crossmax SL/SLS/XL/XLS 29" butted spoke 2

HUB SHELLS

3 N/A HUB BODY
4 V2500901 KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5 V2375601 Kit 110mm axle QRM auto MTB from 2019 DCL
6 N/A HUB BODY
7 V2372401 KIT 110mm AXLE QRM AUTO MTB > 2019

OPTIONS

V2374401 TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8 V2372501 15mm MTB Axle Cap QRM Auto From 2019
99694101 ADAPTER Ft 15 to 9mm QR



CROSSMAX XL 29

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
Multifunction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
2 replacement spokes with each wheel	
Fore adjustment wrench	
Fore adjustment wrench	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separately)	
Freewheel: Shimano HG9, XD or Micro Spline	
Freewheel: Shimano HG9, XD or Micro Spline	
Rear axle: 12x148 Boost thru axle	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- Material : Mxxtal
- Material : Mxxtal
- Material : Mxxtal
- Material : S6000 Aluminum
- Material : S6000 Aluminum
- Height : 22 mm
- SUP
- SUP
- Internal width : 30 mm
- Fore
- Tire : UST Tubeless and tubetype
- Tire : UST Tubeless and tubetype
- Internal width : 30 mm
- Internal width : 30 mm
- Disc brake specific profile
- Asymmetrical rim design
- ETRTO size 29" : 622x30TC
- Black Shield treatment (protects your rim against impacts and scratches)
- ETRTO size 29" : 622x30TC
- ETRTO size 29" : 622x30TC
- Asymmetrical rim design
- Asymmetrical rim design
- ETRTO size 27.5" : 584x30TC
- ETRTO size 27.5" : 584x30TC

WHEEL HUB

- Infinity Hub
- Body : aluminum
- Instant Drive 360
- Axles : Front 15X110 Boost ; Rear 12X148 Boost
- Hub available with 6-bolt or center lock (R) brake rotors
- Body design : INFINITY
- Disc standard : 6 Bolts or Center Lock
- Axle material : aluminum
- Rear body : aluminum
- Axles : Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- Freewheel : Shimano HG MTB / Shimano MS / Sram XD MTB
- Freewheel : FTS-L steel
- Axles : Front 15X110 Boost ; Rear 12X148 Boost
- Infinity Hub
- 24 teeth ratchet
- Hub available with 6-bolt or center lock (R) brake rotors
- Instant Drive 360

VERSIONS

- Disc standard : 6 Bolts or Center Lock (R)
- Disc standard : 6 Bolts or Center Lock (R)

WHEEL WEIGHTS

900