
# MAVIC Crossmax XL 27


2021
FRONT

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included
Recommended tyre sizes: 60mm to 76mm (2.35" to 3.0")

## REFERENCES WHEELS

| | | | |
|---|---|---|---|
| F90522 | Crossmax XL 27,5 Ft Bst* | F91992 | Crossmax XL 27,5 DCL Ft Bst* |




## RIMS



 :

| | | |
|---|---|---|
| 1 | V3766115 | Kit Front/Rear rim Crossmax XL 27,5'' MY21 |

## SPOKES

| | | |
|---|---|---|
| 2 | V2388401 | Kit 12 Front/Rear Crossmax XL 27,5'' butted spoke 279 M7/7 M |

## HUB SHELLS

| | | |
|---|---|---|
| 3 | N/A | HUB BODY |
| 4 | V2500901 | KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP |
| 5 | V2375601 | Kit 110mm axle QRM auto MTB from 2019 DCL |
| 6 | N/A | HUB BODY |
| 7 | V2372401 | KIT 110mm AXLE QRM AUTO MTB > 2019 |

## OPTIONS

| | | |
|---|---|---|
| | V2374401 | TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB |

## ADAPTERS

| | | |
|---|---|---|
| 8 | V2372501 | 15mm MTB Axle Cap QRM Auto From 2019 |
| | 99694101 | ADAPTER Ft 15 to 9mm QR |

Download date: 2024-03-28 / Update date: 2023-03-21

# MAVIC Crossmax XL 27

2021
FRONT

## DELIVERED WITH

| | |
|---|---|
| UST valve and accessories (129 838 01) | |
| Multifonction adjustment wrench (delivered with rear wheel) (325 423 01) | |
| 2 replacement spokes with each wheel | |
| Fore adjustment wrench | |

## COMPATIBILITY

| | |
|---|---|
| Freewheel: Shimano HG9, XD or Micro Spline | |
| Rear axle: 12x148 Boost thru axle | |
| Front axle: 15x110 Boost thru axle | |

## Specifications

### RIMS

- **Material :** Maxtal
- **Material :** S6000 Aluminum
- **Tire :** UST Tubeless and tubetype
- **Internal width :** 30 mm

Black Shield treatment (protects your rim against impacts and scratches)

- **ETRTO size 29" :** 622x30TC

Asymmetrical rim design

- **ETRTO size 27.5" :** 584x30TC

Fore
SUP

### SPOKES

- **Material :** steel
- **Shape :** straight pull, flat, double butted
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless

### WHEEL HUB

Hub available with 6-bolt or center lock (R) brake rotors
Infinity Hub
Instant Drive 360

### VERSIONS

- **Disc standard :** 6 Bolts or Center Lock (R)
- **Hub width :** Boost only (front 110, rear 148)
- **Freewheel :** SRAM XD, Shimano HG9, Shimano Micro-Spline
- **Diameter :** 27,5'' and 29''

### WHEEL WEIGHTS

Weight Front 27.5": 850
Weight Front 29": 900

Download date: 2024-03-28 / Update date: 2023-03-21