

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included Recommended tyre sizes: 25 to 32 mm Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the 2

REFERENZEN RäDER

F92961 Cosmic Elite UST 20 Ft

1



MAVIC Cosmic Elite UST

GELIEFERT MIT

| Mavic tyre sealant (rear wheel) | |
|--|--|
| (355 466 01) | |
| | |
| | |
| Mavic tyre sealant (rear wheel) (355 466 01) | |
| (000 400 01) | |
| | |
| Tyre sealant syringe | |
| l fro obulant offingo | |
| | |
| | |
| Tyre sealant syringe | |
| | |
| | |
| | |
| BR101 quick releases | |
| (M40350 frt, M40351 rear road, M40352 rear MTB) | |
| | |
| | |
| BR101 quick releases (M40350 frt, M40351 rear road, M40352 rear | |
| MTB) | |
| , | |
| UST valve and accessories | |
| (129 838 01) | |
| | |
| | |
| UST valve and accessories | |
| (129 838 01) | |
| | |
| | |
| Pre-installed tubeless rim tape | |
| | |
| | |
| Dur freihilte die bedress der berei | |
| Pre-installed tubeless rim tape | |
| | |
| | |
| User guide | |
| Soo. galdo | |
| | |
| | |
| User guide | |
| | |
| | |
| | |

COMPATIBILITY

| Freewheel: Shimano/Sram, convertible to | |
|---|--|
| Campagnolo with optional driver body | |
| | |
| | |
| | |
| Freewheel: Shimano/Sram, convertible to | |
| Campagnolo with optional driver body | |
| | |
| | |
| Final a la O fal Dalacci a d | |
| Front axle: Quick Release only | |
| | |
| | |
| | |
| Front axle: Quick Release only | |
| ····· | |
| | |
| | |
| | |
| Rear axle: Quick Release only | |
| | |
| | |
| | |
| | |
| Rear axle: Quick Release only | |
| | |
| | |
| | |

Specifications

FELGEN

- Material : S6000 Aluminum - Height: 30 mm Drilling : traditional - Brake track : UB Control - Valve hole diameter: 6.5 mm • Tire : UST Tubeless and tubetype • Material : S6000 Aluminum - Internal width : 17 mm • ETRTO size : 622x17TC ROAD Use with Mavic Tubeless Tape -Height: 30 mm . Drilling : traditional -Brake track : UB Control • Valve hole diameter : 6.5 mm • Tire : UST Tubeless and tubetype - Internal width : 17 mm • ETRTO size : 622x17TC ROAD Use with Mavic Tubeless Tape UST UST UST Tubeless Ready UST Tubeless Ready Down SUP date: 2024-05-17 / Update date: 2023-09-13

RADNABE

• Front and rear bodies : aluminum - Front and rear bodies : aluminum - Axle material : steel - Axle material : steel Sealed cartridge bearings (QRM) Sealed cartridge bearings (QRM) • Freewheel : FTS-L steel • Freewheel : FTS-L steel FTS-L FTS-L QRM QRM VERSIONS

- Color : Black only - Color : Black only

RADGEWICHTE

815