

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included Recommended tyre sizes: 25 to 32 mm Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the 2

REFERENZEN RäDER

R41061 Cosmic Elite UST 20 Rr



MAVIC Cosmic Elite UST

GELIEFERT MIT

Mavic tyre sealant (rear wheel)	
(355 466 01)	
Mavic tyre sealant (rear wheel)	
(355 466 01)	
(
Tyre sealant syringe	
Tyre sealant syringe	
i ji o ooddalle oji migo	
BR101 quick releases	
(M40350 frt, M40351 rear road, M40352 rear	
MTB)	
BR101 quick releases	
(M40350 frt, M40351 rear road, M40352 rear	
MTB)	
,	
UST valve and accessories	
(129 838 01)	
UST valve and accessories	
(129 838 01)	
Der fredelle dit beleve der bere	
Pre-installed tubeless rim tape	
Pre-installed tubeless rim tape	
Lloor quido	<u> </u>
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to	
Campagnolo with optional driver body	
Freewheel: Shimano/Sram, convertible to	
Campagnolo with optional driver body	
Final a la O fal Dalacci a d	
Front axle: Quick Release only	
Front axle: Quick Release only	
·····	
Rear axle: Quick Release only	
Rear axle: Quick Release only	

Specifications

FELGEN

SUP

- Material : S6000 Aluminum - Height: 30 mm Drilling : traditional - Brake track : UB Control - Valve hole diameter: 6.5 mm • Tire : UST Tubeless and tubetype • Material : S6000 Aluminum - Internal width : 17 mm • ETRTO size : 622x17TC ROAD Use with Mavic Tubeless Tape -Height: 30 mm . Drilling : traditional -Brake track : UB Control • Valve hole diameter : 6.5 mm • Tire : UST Tubeless and tubetype - Internal width : 17 mm • ETRTO size : 622x17TC ROAD Use with Mavic Tubeless Tape UST UST UST Tubeless Ready UST Tubeless Ready Down SUP date: 2024-05-16 / Update date: 2023-09-13

RADNABE

• Front and rear bodies : aluminum - Front and rear bodies : aluminum - Axle material : steel - Axle material : steel Sealed cartridge bearings (QRM) Sealed cartridge bearings (QRM) • Freewheel : FTS-L steel • Freewheel : FTS-L steel FTS-L FTS-L QRM QRM VERSIONS

- Color : Black only - Color : Black only

RADGEWICHTE

955