

2021 REAR

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm $\,$

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesnn't exceed 120kg, bike included

Recommended tyre sizes: 25 to 32 mm

Max. Pressure: see indication on wheel and tyre. If they differ, use the lowest of the $2\,$

REFERENZEN RäDER

R41061 Cosmic Elite UST 20 Rr

MAVIC Cosmic Elite UST

GELIEFERT MIT

Mavic tyre sealant (rear wheel) (355 466 01)	
Mavic tyre sealant (rear wheel) (355 466 01)	
Tyre sealant syringe	
Tyre sealant syringe	
BR101 quick releases (M40350 frt, M40351 rear road, M40352 rear MTB)	
BR101 quick releases (M40350 frt, M40351 rear road, M40352 rear MTB)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
Pre-installed tubeless rim tape	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to	
Campagnolo with optional driver body	
Franchael Chimana/Cram convertible to	
Freewheel: Shimano/Sram, convertible to	
Campagnolo with optional driver body	
Front axle: Quick Release only	
· · · · · · · · · · · · · · · · · · ·	
Front axle: Quick Release only	
Rear axle: Quick Release only	
Tiodi dalo. Quick ficicase offiy	
Rear axle: Quick Release only	
·	
I	

Specifications

FELGEN

- Material: S6000 Aluminum - Height: 30 mm • Drilling: traditional - Brake track : UB Control - Valve hole diameter: 6.5 mm • Tire: UST Tubeless and tubetype - Material: S6000 Aluminum • Internal width: 17 mm ■ ETRTO size: 622x17TC ROAD Use with Mavic Tubeless Tape - Height: 30 mm - Drilling: traditional

- Brake track : UB Control • Valve hole diameter: 6.5 mm • Tire: UST Tubeless and tubetype - Internal width: 17 mm ■ ETRTO size: 622x17TC ROAD Use with Mavic Tubeless Tape UST

UST Tubeless Ready UST Tubeless Ready
Down SUP date: 2024-05-16 / Update date: 2023-09-13

RADNABE

• Front and rear bodies : aluminum • Front and rear bodies : aluminum -Axle material : steel -Axle material: steel Sealed cartridge bearings (QRM) Sealed cartridge bearings (QRM) • Freewheel: FTS-L steel •Freewheel: FTS-L steel

FTS-L FTS-L QRM QRM

VERSIONS

- Color : Black only - Color : Black only

RADGEWICHTE

955

SLIP