

2022 FRONT

Maximum tyre pressure: 4.4bar/64PSI with a 28mm tyre - 2.6bar/38PSI with a 64mm tyre

ASTM CATEGORY 2 : road and offroad with jumps less than 15cm

For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 120kg, bike included


Maximum tyre pressure: 6.75bar/97PSI with a 23mm tyre - 3.8bar/55PSI with a 62mm tyre

Recommended tire sizes: 25 to 32 mm

Max. Pressure: see indication on wheel and tire. If they differ, use the lowest of the 2

Maximum tyre size: width 62mm - pressure max. 3.8Bar/55PSI

REFERENCES WHEELS F92571 KSYRIUM 30 CL 700 12x100





RIMS



:

1	V00004531	Kit Front/Rear rim Ksyrium 30 Disc	
	V3720101	25mm UST Tape for 19 to 22mm Road Rims	

SPOKES

2 V00005131 Kit 12 Front/Rear Ksyrium 30 Disc butted spoke 287mm + black

HUB SHELLS

3	N/A	HUB BODY
4	M40129	KIT 2 BEARINGS 6902 15x28x7
5	V2373301	KIT QRM AUTO FRONT AXLE 12mm > 2019

ADAPTERS

6	V2680501	12mm Road Axle Cap QRM Auto
•	12000001	12mm Hoda 7 kilo dap driw 7 lato
	V2680301	"Kit Ft Road Adapter 12 >> 9mm"

MAVIC KSYRIUM 30 DISC

DELIVERED WITH

Mavic tyre sealant (rear wheel) (355 466 01)	
Front QR adapters	
Front QR adapters	
Rear QR adapters for Instant Drive 360 (B49 894 01)	
Rear QR adapters for Instant Drive 360 (B49 894 01)	
UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
Pre-installed tubeless rim tape	
User guide	
User guide	

COMPATIBII ITY

COMPATIBILITY	
Freewheel: Shimano/Sram, convertible to Campagnolo ED11, N3W and XD-R with optional driver bodies	
Front axle: 12x100 thru axle, easily convertible to quick release with included adapters. Not compatible with 15mm through axles.	
Freewheel body: convertible SRAM XD road (kit V2580101 sold separately)	
Rear axle: 12mm thru axle, convertible to Quick Release with included adapters	
Freewheel body: convertible SHIMANO HG light road (kit V3850101 sold separately)	
Freewheel body: convertible SHIMANO MS (kit V3990101 sold separately)	
Freewheel body: convertible CAMPAGNOLO ED (kit V3440101 sold separately)	
Front axle: 12x100 thru axle, easily convertible to quick release with included adapters. Not compatible with 15mm through axles.	
FTS-L Shimano / Sram freewheel body ([30871101] - Delivered on the wheel)	
ID360 Sram XD freewheel body ([V3740101])	
Rear axle: for fixing nuts only (included), M9x1 thread	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	
ID360 Shimano Micro Spline alloy freewheel body ([V3990101])	

Specifications

RIMS

- Material : Maxtal - Material : Maxtal - Height: 30 mm - Height: 30 mm

■ Joint : SUP welding technology - Joint: SUP welding technology - Drilling: traditional Internal width: 19 mm Disc brake specific profile • Tire: UST Tubeless and tubetype

 $\hbox{\bf - Drilling:} \ \ traditional$ - Internal width: 19 mm Disc brake specific profile

ETRTO size: 622x19TC Downlo**et RTO** size 4 622x1916 pdate date: 2024-02-15

-Tire: clincher

WHEEL HUB

- Body: aluminum Infinity hubs

• Front and rear bodies : aluminum -Axle material : aluminum Instant Drive 360 freewheel technology QRM Auto bearing preload technology

• Front: Quick release and 12x100 through axle compatible

-Rear: Quick Release, 12x142 and 12x135

compatible

Hub available for Center Lock brake rotors only

- Body design: INFINITY

 Disc standard : Center Lock® only ■ Axle material: aluminum

-Axle size: front 12x100 / rear 12x142 -Convertible to quick release with included adapters

WHEEL WEIGHTS

823