

2022 FRONT

ASTM CATEGORY 3: CROSS COUNTRY


For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included

Maximum tyre pressure: 4.1bar/59PSI with a 28mm tyre - 2.45bar/36PSI with a 64mm tyre Recommended tire sizes: 28 to 64 mm (1.1" to 2.5")

REFERENCES WHEELS

F92671 CROSSMAX INT 29 BST F93661 CROSSMAX INT 29

F92681 CROSSMAX CL 29 BST





RIMS



:

1	V3766715	Kit Front/Rear rim Crossmax 22 29"	
	V2700101	UST Tape 28mm for 25 to 27mm wide rims	

SPOKES

2	V2381401	KIT 12 FT/RR BUTTED SPOKES 296mm MTB 29"
---	----------	--

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019
6	N/A	HUB BODY
7	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL
9	N/A	HUB BODY
10	V2372301	KIT 100mm AXLE QRM AUTO MTB > 2019
	V2374501	KIT 12mm FRT AXLE D6T QRM Auto Allroad 19

OPTIONS

V2374401 TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	99694101	ADAPTER Ft 15 to 9mm QR

MAVIC CROSSMAX 29

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
Pre-installed tubeless rim tape	
User guide	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

CUMPATIBILITY	
Front axle: convertible from 15mm thru axle to Quick Release with adapters (delivered with non-boost wheel)	
Rear axle: 12mm thru axle, convertible to Quick Release with adapters (delivered with non-boost wheel)	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Front axle adapters: 15x100 convertible to 9x100 (kit 99694101 sold separetly)	
Front axle adapters: 15x110 convertible to 9x110 (kits 99694101 + V2372501 sold separetly)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
ID360 Sram XD freewheel body ([V3740101])	
Front axle: for fixing nuts only (included), M9x1 thread	
Rear axle: for fixing nuts only (included), M9x1 thread	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9Ű. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	

Specifications

RIMS

Material : MaxtalMaterial : MaxtalHeight : 21 mm

Joint: SUP welding technology
 Joint: SUP welding technology
 Drilling: traditional
 Internal width: 25 mm

• Valve hole diameter: 6.5 mm • Drilling: traditional • Internal width: 25 mm

Disc brake specific profile
E-Bike specific rim profile
E-Brito size 29": 622x25TSS
Use with Mavic Tubeless Tape
ETRTO size 29": 622x25TSS
Asymmetrical rim design

• Tire : clincher UST Tubeless Ready SPOKES

• Material : steel • Material : steel

Shape: straight pull, flat, double butted
 Shape: j-bent, round, 2.0 straight gauge

Nipples: steel, ABS
Count: 24 front and rear
Lacing: front and rear crossed 2
R2R carbon spoke technology

WHEEL HUB

- Body: aluminum Infinity hubs

Instant Drive 360 freewheel technology QRM Auto bearing preload technology

Hub available with 6-bolt or Center Lock® brake rotors

- Axles: Front 15X110 (Boost) or 15x100; Rear 12X148 (Boost) or 12x142

- Body design : INFINITY - Disc standard : $6 \; \text{Bolts} \; \text{or Center Lock} \hat{\mathbb{A}} \otimes$

-Axle material : aluminum

Rear body: aluminumAxle size: front 15x100 / rear 12X142 -

Axie size: front 15x100 / rear 12x142 Convertible to quick release with included adapters
 Axies: Front 15X110 (Boost) or 15x100; Rear

12X148 (Boost) or 12x142

- Freewheel: Shimano HG MTB / Shimano MS /

Sram XD MTB • Freewheel: FTS-L steel

VERSIONS

Disc standard: 6 Bolts or Center Lock®
 Hub width: Boost (front 110, rear 148) or Non-Boost (front 100, rear 135/142) 6 bolts
 Freewheel: SRAM XD, Shimano HG9, Shimano Micro-Spline

WHEEL WEIGHTS

820

Download date: 2024-04-18 / Update date: 2024-04-10