
MAVIC CROSSMAX XL R 29

ASTM CATEGORY 4 : ENDURO AND TRAIL RIDING
Maximum tyre pressure: 2.35bar/34PSI with a 52mm tyre - 1.25bar/18PSI with a 125mm tyre
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Minimum tyre size: width 52mm - pressure max. 2.35Bar/34PSI
Recommended tire sizes: 50mm to 76mm (2.0" to 3.0")

REFERENCES WHEELS

F92971	CROSSMAX XL R INT 29 BST	F92981	CROSSMAX XL R CL 29 BST



RIMS



 :

1	V00004931	Kit Front/Rear rim Crossmax XLR 29''
	V3750101	35mm UST Green Tape for 30mm wide rims

SPOKES

2	V2389101	Kit 12Fr/Rr XmaxSL Ultimate spk293+np&w while stock last
2	V00065231	Kit 12 Front/Rear Crossmax SL Ultimate 29'' butted stainless

HUB SHELLS

3	N/A	HUB BODY
4	V2500901	KIT BEARINGS 18x30x7 + WAVED WASHER + CLIP
5	V2372401	KIT 110mm AXLE QRM AUTO MTB > 2019
6	N/A	HUB BODY
7	V2375601	Kit 110mm axle QRM auto MTB from 2019 DCL

OPTIONS

	V2374401	TORQUE CAPS 15*31 Adapter MTB QRM Auto > 2019 Frt HUB

ADAPTERS

8	V2372501	15mm MTB Axle Cap QRM Auto From 2019
	99694101	ADAPTER Ft 15 to 9mm QR

Download date: 2024-03-28 / Update date: 2024-02-15

MAVIC CROSSMAX XL R 29

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
Pre-installed tubeless rim tape	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
User guide	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Front axle: 15x110 Boost thru axle	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Boost Axles : 15X110 ; 12X148	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Instant Drive 360 freewheel technology The new Instant Drive 360 freewheel system is super light and fast to engage with only 9Â°. A large contactless rubber seal provides low friction, while a wide array of end caps makes it super versatile.	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- **Material :** 100% carbon fiber with UDÂ² external layer
- **Material :** 100% carbon fiber with UDÂ² external layer
- **Height :** 25 mm
- **Drilling :** traditional
- **Internal width :** 30 mm
- **Drilling :** traditional
- **Internal width :** 30 mm

Disc brake specific profile
E-Bike specific rim profile
Hookless profile

- **ETRTO size 29" :** 622x30TSS
- **ETRTO size 29" :** 622x30TSS

Asymmetrical rim design

- **Tire :** clincher

UST Tubeless Ready

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** straight pull, flat, double butted
- **Shape :** j-bent, round, 2.0 straight gauge
- **Nipples :** aluminum, ABS
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless

R2R carbon spoke technology

WHEEL HUB

Infinity hubs

- **Body :** aluminum

Instant Drive 360 freewheel technology
QRM Auto bearing preload technology
Hub available with 6-bolt or Center LockÂ® brake rotors

- **Body design :** INFINITY
- **Disc standard :** 6 Bolts or Center LockÂ®
- **Axle material :** aluminum
- **Rear body :** aluminum
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Rear :** Quick Release, 12x142 and 12x135 compatible
- **Freewheel :** FTS-L steel

VERSIONS

- **Disc standard :** 6 Bolts or Center LockÂ®
- **Hub width :** Boost only (front 110, rear 148)
- **Freewheel :** SRAM XD, Shimano HG9, Shimano Micro-Spline

WHEEL WEIGHTS

735

Download date: 2024-03-28 / Update date: 2024-02-15