
MAVIC CROSSMAX SL ULTIMATE 25 29

ASTM CATEGORY 3 : CROSS COUNTRY
For a longer longevity of the wheel, Mavic recommends that the total weight supported by the wheels doesn't exceed 150kg, bike included
Maximum tyre pressure: 4.1bar/59PSI with a 28mm tyre - 2.45bar/36PSI with a 64mm tyre

REFERENCES WHEELS

R41311	XMAXSLULT 25 INT 29 BST HG	R41331	XMAXSLULT 25 CL 29 BST MS
R41321	XMAXSLULT 25 INT 29 BST XD		



RIMS



 :

1	V00004831	Kit Front/Rear rim Crossmax SL Ultimate 29'' 22
	V2700101	UST Tape 28mm for 25 to 27mm wide rims

SPOKES

2	V00065231	Kit 12 Front/Rear Crossmax SL Ultimate 29'' butted stainless
2	V2389101	Kit 12Fr/Rr XmaxSL Ultimate spk293+np&w while stock last

HUB SHELLS

3	N/A	HUB BODY
4	M40076	HUB BEARINGS 17x30x7 6903 x 2
5	V2375701	Kit ID360 148 DCL axle with circlip
6	V2252701	KIT ID360 INSERT SHAPED EAR LOBE > 2017
7	V00063631	Kit ID360 seal version 2 (larger)
8	V2375201	KIT ID360 24 TEETH 2 RATCHET + MTB SPRING + PAD (specific)
9	V2375401	KIT ID360 MTB 24T 3 NOISE REDUCING PADS
10	V2372901	KIT 3 ID360 MTB SPRINGS
11	V3990101	MicroSpline MTB Freewheel Body ID360
11	V3780101	HG9 Alloy MTB Freewheel Body ID360
11	V3740101	XD MTB Freewheel Body ID360
12	V2373001	KIT ADJUST. SYSTEM QRM AUTO ID360 for 17x30x7 bearing
13	N/A	HUB BODY
14	V2372201	KIT ID360 148 D6T AXLE WITH CLIP

OPTIONS

8	V2372801	KIT ID360 2x40 TEETH RATCHETS + MTB SPRING + GREASE + PAD

ADAPTERS

15	V2510701	ID360V2RrAxleAdapt12x142/148
	V2510801	ID360 V2 RrAxleAdapt9x135

Download date: 2024-03-29 / Update date: 2024-02-15

MAVIC CROSSMAX SL ULTIMATE 25 29

DELIVERED WITH

UST valve and accessories (129 838 01)	
UST valve and accessories (129 838 01)	
Pre-installed tubeless rim tape	
Multifonction adjustment wrench (delivered with rear wheel) (325 423 01)	
Wheelbag (V24 801 01)	
Wheelbag (V24 801 01)	
User guide	
2 replacement spokes with each wheel	
2 replacement spokes with each wheel	

COMPATIBILITY

Freewheel body: convertible SHIMANO MS (kit V3990101 sold separately)	
Front axle: 15x110 Boost thru axle	
Freewheel body: convertible SHIMANO HG MTB steel (kit V3790101 sold separately)	
Rear axle adapters: 12x148 convertible to 9x141 (kit V2510801 sold separetly)	
Rear axle: 12x148 Boost thru axle	
Front axle: 15x110 Boost thru axle	
Front axle: for fixing nuts only (included), M9x1 thread	

Specifications

RIMS

- **Material :** 100% carbon fiber with UDÂ² external layer
- **Material :** 100% carbon fiber with UDÂ² external layer
- **Height :** 25 mm
- **Drilling :** traditional
- **Internal width :** 25 mm
- **Drilling :** traditional
- **Internal width :** 25 mm

Disc brake specific profile
E-Bike specific rim profile

- **ETRTO size 29" :** 622x25TSS

Hookless profile

- **ETRTO size 29" :** 622x25TSS

Adaptive Layup Carbon technology

- **Tire :** clincher

UST Tubeless Ready

SPOKES

- **Material :** steel
- **Material :** steel
- **Shape :** straight pull, flat, double butted
- **Shape :** j-bent, round, 2.0 straight gauge
- **Nipples :** aluminum, ABS
- **Count :** front 18, rear 24
- **Count :** 24 front and rear
- **Lacing :** front and rear crossed 2, contactless

R2R carbon spoke technology

WHEEL HUB

Infinity hubs

- **Body :** aluminum

Instant Drive 360 freewheel technology
QRM Auto bearing preload technology
Hub available with 6-bolt or Center LockÂ® brake rotors

- **Axles :** Front 15X110 Boost ; Rear 12X148 Boost
- **Body design :** INFINITY
- **Disc standard :** 6 Bolts only
- **Axle material :** aluminum
- **Rear body :** aluminum
- **Axles :** Front 15X110 (Boost) or 15x100 ; Rear 12X148 (Boost) or 12x142
- **Front :** Quick release, 12x100 and 15x100 through axle compatible
- **Freewheel :** FTS-L steel

VERSIONS

- **Disc standard :** 6 Bolts or Center LockÂ®
- **Hub width :** Boost only (front 110, rear 148)
- **Freewheel :** SRAM XD, Shimano HG9, Shimano Micro-Spline

WHEEL WEIGHTS

740

Download date: 2024-03-29 / Update date: 2024-02-15